Hard - to - Find Catalog





products • service • education



"FUG"

the Weevil

Development

Thank you for taking the time to consider this catalog. Our purpose is to offer Hard to Find items used for the unique niche of fumigation. The fumigation industry has changed greatly over the last 10 years and continues to change. Finding the needed equipment and devices can be very time consuming, and the trial and error to come up with final products can be very expensive. Items in this catalog represent those efforts and trials we and others have made over the last 23 years.

This catalog is not a final product, nor the items are the only items that will be in this catalog. We will continue to update the items and post the most current catalog on our website at:

www.FumigationZone.com

If you are aware of something that should be included, please call us at 800-992-1991.

Important Consideration

Due to the unique nature of these items, it may take some time to order. Please take this into consideration when ordering, because assembly may take some time. We do stock much of what we provide in the catalog. We even stock many items which do not appear as items, but may make up components or variations of posted equipment. There is not a practical way to keep everything in stock, but we will make every effort to fulfill your specific needs as quickly as possible.



Danger and Health Considerations

Many of these items are specific to the type of characteristics with a fumigant or fumigant form. High pressure hazards pose a risk to health and even life. Using parts or components not rated for proper pressure can cause an explosion and send fragments of metal, plastic, or other materials out at extremely high speeds. ALWAYS RESPECT HIGH PRESSURE AND ENSURE YOU ARE USING APPROPRIATELY RATED COMPONENTS. We will provide on-line high pressure gas application safety training (upon request). It is always best to seek training by professional gas application specialists.

Other Services

In addition to the sale of these products, we provide consultation, site specific system development, on-site installation, and annual maintenance packages. Large Projects include fixed central gas application systems with web access to data. Please challenge us with ideas you have and we will work with you to develop safe, successful solutions.

USDA Regulations

Some Items provided are required for certain USDA gas applications. The USDA has strict, safe measures that require specific equipment. These items are marked by • ** after item name/description.

Thank you again for letting us assist with your needs. Many more safe, successful, and fun fumigations to you.







Fumigation Monitoring Equipment Description	Sizes	Item #
Calibration Kit	01262	HM101
Kit includes a brass single stage regulator - 3000 psi. inlet, 30 psi.		ПІИТОТ
outlet. Fittings for 1/4 in. tubing. Includes 2 durable fill bags,	regulator	HM101-R
4 ft. of 1/4 in. poly tubing, and 2 1/4 in. tubing unions.	regulator	11111101-10
Regulator has a stainless steel diaphram.		
2 extra bags - (2 liter)	2 bags	HM101-B
Calibration Cylinder	2 bago	TIMITOT B
If you do not possess a cylinder for calibrating, then these will be		
good cylinders for the kit. FSS, Inc. Will Not refill these cylinders.		
10000 ppm of Sulfuryl Fluoride		HM102-S
10000 ppm of Methyl Bromide		HM102-M
5 ppm of Sulfuryl Fluoride		HM102-I
Colorimetric Tube Pump - **		
This tube pump measures 100 ccs for every pump. Bellow style.		HM103
Uses colorimetric tubes. All associated tubes can be used as		
suitable clearing devices if specific ppm range is indicated.		
OFSS I		
Carbon Dioxide CO2 Tubes - **		
Use Tubes with the Tube Pump		
Measures 100 ppms to 3000 ppms		HM104-1
Measures 1000 ppms to 60000 ppms		HM104-2
Measures 50000 ppms to 600000 ppms		HM104-3
Methyl Bromide MB Tubes - **		
Use Tubes with the Tube Pump		1111405.4
Measures .2 ppms to 8 ppms		HM105-1
Measures .5 ppms to .30 ppms		HM105-2
Measures 3 ppms to 100 ppms		HM105-3
Phosphine PH3 Tubes - **		
Use Tubes with the Tube Pump		
Measures .1 ppms to 4 ppms		HM106-1
Measures .1 ppms to 15 ppms		HM106-2
Measures 15 ppms to 1000 ppms		HM106-3



	Fumigation Service & Supply, Inc.		
Fumigation Monitoring	Equipment Description	Sizes	Item #
Hy	drobromic/Hydrochloric Acid Tubes - ** Use Tubes with the Tube Pump		
100	Measures 1 ppms to 10 ppms		HM107-1
	Measures 2 ppms to 20 ppms		HM107-2
	Measures 50 ppms to 5000 ppms		HM107-3
Fui	miscope - **		HM108
D	Measures both Methyl Bromide and Sulfuryl Fluoride up to 2700 oz. or gr./M3 with precise accuracy. Will not give exact ppm count. Thermal conductivity sensor. Runs on 115 or 220 volt.		
	Remote Data Model		HM108-R
Ex	plorIR - Low Range SF		HM109
SF-ExplorIR™	Legal clearing device for Sulfuryl Fluoride. Measures 0 - 100 ppms of SF with precise accuracy. Very rugged light weight unit. Comes with long lasting lithium battery and charge kit. ISO 9001 certified. Uses Infrared technology. This unit has upgradable software-so no need to buy full price new models.		
Re	portIR - High Range SF		HM110
	Single zone monitor that measures Sulfuryl Fluoride in high ranges. Measures 5 - 50000 ppms with great accuracy, using Infrared technology. Can use with hub for remote data Collection. This unit has upgradable software-so no need to buy full price new models.		11111110
Re	portIR - High Range PH3		HM111
36 spectros	Single zone monitor that measures Phosphine in high ranges. Measures 5 - 50000 ppms with great accuracy, using Infrared technology. Can use with hub for remote data Collection. This unit		
	has upgradable software-so no need to buy full price new models.		
Re	portIR - High Range MB - ** Single zone monitor that measures Methyl Bromide in high ranges.		HM112
	Measures 5 - 50000 ppms with great accuracy, using Infrared technology. Can use with hub for remote data Collection. This unit has upgradable software-so no need to buy full price new models.		



	,g		
Fumigation Monito	ring Equipment Description	Sizes	Item #
	Spectros Multiport SF - MB - PH3 Multi zone monitor measures up to 16 zones of Sulfuryl Fluoride,	SF	HM113-S
* spectros	Methyl Bromide, or Phosphine in high ranges from 0 - 50000 ppms with great accuracy. Uses Infrared technology. Need specifics	MB	HM113-M
	for custom build when ordering. Can use with hub for remote data collection which is downloadable to computer or printer.	PH3	HM113-P
	Spectros - Transportable Transportable monitors that are rugged and compact for demanding point of use needs for all types of situations. Many different monitors can be custom built. Please call FSS, Inc. for inquiries.		HM114
	Interscan 1900 Measures 0 to 50 ppms of Sulfuryl Fluoride. Heavier than an ExplorIR - Low Range SF. Used as a clearing device. Requires multiple calibrations per year. Calibration kit not included in price.		HM115
	Battery and Charger	battery pack	HM115-B
Manage Control of the	Photo Ionization Device Device is used to detect leaks, and can detect ppms in ambient air from 0.0 to 1000 ppms of Methyl Bromide. This is NOT used as a clearance device. Long lasting battery and light weight makes this unit great for travel around a job site.		HM116
SILO CHEK FPM Prosphine Pumigation Monitor Light on to control	SiloChek - ** Not used as a clearing device. High range Phosphine monitor has digital display and internal pump. Reads with great accuracy.		HM117
	Pac 7000 - **		HM118
	Used as a clearing device for Phosphine. Low range monitor has		



Custom equipment can be ordered. Contact FSS, Inc. for pricing. All items have been field tested and proven successful for intended use.

digital display and internal pump. Utilizes electrochemical sensor.



	Fumigation Service & Supply, Inc.		
<mark>umigation Moni</mark> t	toring Equipment Description	Sizes	Item #
	PortaSens Leak Detector Not used as a clearing device. Can be either high or low range, but	high range	HM119-H
35000	not both. Phosphine monitor with digital display and internal pump. Utilizes electrochemical sensor.	low range	HM119-L
au fair	X AM2000		HM120
	Not used as a clearing device. Confined space monitor measures Oxygen, Carbon Monoxide, and Explosive gases, but does not have a sensor placed in unit for Phosphine. This is used for safety in confined spaces where a fumigator might be exposed to potentially hazardous gas levels that are not fumigant based.		
- COLUMN	X AM5000 - Confined Space		HM121
His	Not used as a clearing device. Confined space monitor measures Oxygen, Carbon Monoxide, Explosive gases, and can have a sensor placed in unit for Phosphine. This is used for safety in confined spaces where a fumigator might use Phosphine.		
	Add a Phosphine sensor		HM121-P
	Passport 5 Star Not used as a clearing device. Confined space monitor measures Oxygen, Carbon Monoxide, and Explosive gases, but does not have a sensor placed in unit for Phosphine. Can measure other gases in confined spaces where a fumigator might be exposed to potentially hazardous gas levels that are not fumigant based.		HM122
CEA 700 CO ₂ 732 ppm 68.5 °F TEMPERATURE	Carbon Dioxide Monitor - Low Range Used as a clearing device. Measures 0 to 10000 ppm with high accuracy for safe monitoring.		HM123
	Carbon Dioxide Monitor - High Range		HM124
	Full range monitor measures 0% to 100% X volume of CO2 with high accuracy. When dealing with high concentrations of CO2, it is important to make sure Oxygen (O2) levels are sufficient.		



Fumigation Monitoring E	quipment Description	Sizes	Item #
Mon	Includes 18 quick Connect (QC) panel mounts for 1/4 in. monitoring line. Easy fold up design for "on the go" fumigators. Very durable. Includes 4 QC bodies for 1/4 in. monitoring line. 10 extra bulkhead panel mounts and 4 b.h. connectors bodies.		HM125 HM125-1
Mon	itoring Box with Pump		HM126
	Same as above box and includes a high powered, gas tight pump for monitoring line more than 100 ft. from zone. Easy fold up design for "on the go" fumigators. Very durable. Includes 4 QC bulkhead connectors for 1/4 in. monitoring line. Pump Only	pump	HM126-P
	Monitoring equipment is expensive, so please choose the right equipment. We will assist with choosing the correct monitoring equipment for your specific needs. There are other monitoring devices we use, but do not post them in this catalog. Call us for inquiries about other monitoring equipment. The best way to fumigate is to be safe and to know about the gas you use.	- 2h	



Methyl Bromide (ME	3) Fumigation Equipment Description	Sizes	Item #
	MB Cylinder Adapter		HMB101
	Hook up to a cylinder of MB.		
	Wrench required.		
	Hand Tight Adapter		HMB101-H
*	Hook up to a cylinder of MB.		
	No wrench required.		
	Application Tubing - Shoot Line (MB)		
	3/8 in. OD tubing used primarily for the application of MB		
	100 ft. length	100 ft	HMB102-1
1	250 ft. length	250 ft	HMB102-2
	500 ft. length	500 ft	HMB102-3
	Jumpers are small lines for disconnecting after gas application	12 ft	HMB102-4
	Monitor Tubing - Monitor Line (MB)		
	1/4 in. OD tubing used primarily for monitoring MB	400 %	
	100 ft. length	100 ft	HMB103-1
	250 ft. length	250 ft	HMB103-2
	500 ft. length	500 ft	HMB103-3
	Jumpers are small lines for disconnecting after gas application Connector	12 ft	HMB103-4
	Shoot line union for hooking up extra lengths of shoot line	10 pook	HMB104-S
1 1 1 m	Shoot line union for hooking up extra lengths of shoot line	10 pack	HIVID 104-3
	Monitor line union for hooking up extra lengths of monitor line	10 pack	HMB104-M
	Mornitor line dilion for flooking up extra lengths of mornitor line	10 pack	HIVID 104-IVI
	Branch Tee		
	Branch shoot line from 1 line into 2 lines in perpendicular form	10 pack	HMB105-S
	Branch monitor line from 1 line into 2 lines in perpendicular form	10 pack	HMB105-M
	Y - Tee		
19/10	Branch shoot line from 1 line into 2 lines in Y form	10 pack	HMB106-S
60			
(0.30	Branch monitor line from 1 line into 2 lines in Y form	10 pack	HMB106-M
-			



	rumigation Service & Supply, Inc.		
Methyl Bromide (MI	B) Fumigation Equipment Description	Sizes	Item #
	Elbow		
	Union for shoot line at a 90 degree angle	10 pack	HMB107-S
	Union for monitor line at a 90 degree angle	10 pack	HMB107-M
	Reducer - Expander		
	Reduces/expands shoot line into monitor line size or vice versa	10 pack	HMB108
	Ball Valve		
	Ball valve for shoot line		HMB109-S
376	Ball valve for monitor line		HMB109-M
	Check Valve		
	1 way flow valve for shoot line		HMB110-S
	1 way flow valve for monitor line		HMB110-M
	Shoot Line Manifold for MB		
	Manifolds are available for MB fumigations, but not recommended unless under extreme circumstance or unsafe situations necessitate such use. They are expensive to build and the fumigator loses some control over shoot line safety. Please call		HMB111-X
	FSS, Inc. more for information regarding MB shoot line manifolds.		
400	Vaporizer - Electric - **	25lb/r	nin HMB112-1
	Vaporizes liquid MB into gas form using electric heat elements. Meets USDA standards for vaporizing Gas. You need to know what flow rate MB is coming into vaporizer before buying. These	12.5lb/r	nin HMB112-2
	are 3 phase units. Can use CO2 with these units. Call FSS, Inc. for more information.	6.2lb/r	nin HMB112-3



	rumigation Service & Supply, Inc.		
Methyl Bromide (MB) F	Fumigation Equipment Description	Sizes	Item #
Va	aporizer - Propane - ** Vaporizes liquid MB into gas form using propane to heat elements. Meets USDA standards for vaporizing Gas.		HMB113
M	B Dispenser		HMB114
	Connect to a cylinder using an adapter, and dispense .25 to 5 lbs. of MB at a time. Has pressure release valves for assisting refill.		
Hi	gh Quality Connection Fittings		
	These connection fittings can be used for MB gas applications and MB and SF monitoring. These medium pressure fittings CAN NOT be used for safe SF gas application because gas pressures can be too great. They are very durable and long lasting, and have proven very successful for vacuums that pumps generate when monitoring.		
Ma	ale Plug - SF and MB		
	Male plug for shoot line union ends	10 pack	HQ102-S
	Male plug for monitor line union ends	10 pack	HQ102-M
Fe	emale Cap - SF and MB		
	Female plug for shoot line ends	10 pack	HQ103-S
	Female plug for monitor line ends	10 pack	HQ103-M
Co	onnector		
Contract of the Contract of th	Shoot line union for hooking up extra lengths of shoot line	10 pack	HQ104-S
	Monitor line union for hooking up extra lengths of monitor line	10 pack	HQ104-M



Methyl Bromide (MB)	Fumigation Equipment Description	Sizes	Item #
	Branch Tee		
	Branch shoot line from 1 line into 2 lines in perpendicular form	10 pack	HQ105-S
	Branch monitor line from 1 line into 2 lines in perpendicular form	10 pack	HQ105-M
<u>\</u>	Y - Tee		
Carlo II	Branch shoot line from 1 line into 2 lines in Y form	10 pack	HQ106-S
	Branch monitor line from 1 line into 2 lines in Y form	10 pack	HQ106-M
E	Elbow		
	Union for shoot line at a 90 degree angle	10 pack	HQ107-S
	Union for monitor line at a 90 degree angle	10 pack	HQ107-M
En F	Reducer - Expander		
	Reduces/expands shoot line into monitor line size or vice versa	10 pack	HQ108-U
	Reduces shoot line into monitor line from a connector	10 pack	HQ108-R

Sulfuryl Fluoride Equipment



Sulfuryl Fluoride (S	SF) Fumigation Equipment Description	Sizes	Item #
	SF Cylinder Adapter		HSF101
	Hook up to a cylinder of SF.		
M .	Wrench required.		
	Hand Tight Adapter	3/8 in. QC	HSF101-S
	Hook up to a cylinder of SF.	1/4 in. QC	HSF101-M
	No wrench required. Highly recommended.		
	Application Tubing - Shoot Line (SF)	100 ft	HSF102-1
	3/8 in. OD tubing used primarily for the application of SF	250 ft	HSF102-2
	Colors include - Red, Orange, Yellow, Green, Purple, Blue	500 ft	HSF102-3
	Can come on an 11 in. spool - just add C to end of Item #	w/spool	add C
	11 in. replacement spool	spool only	HSF102-S
	Jumpers are small lines for disconnecting after gas application	12 ft	HSF102-J
	Monitor Tubing - Monitor Line (SF)	100 ft	HSF103-1
	1/4 in. OD tubing used primarily for monitoring SF, but can be used	250 ft	HSF103-2
	for shoot line as well. Red, Orange, Yellow, Green, Purple, Blue	500 ft	HSF103-3
600	Can come on a 6 in. spool - just add C to end of Item #	w/spool	add C
	6 in. replacement spool	spool only	HSF103-S
	Jumpers are small lines for disconnecting after gas application	12 ft	HSF103-J
	Connector Chapt line union for healting up outre longths of chapt line		1105404.4
	Shoot line union for hooking up extra lengths of shoot line		HSF104-1
	Monitor line union for hooking up extra lengths of monitor line		HSF104-2 HSF104-3
	2 piece solid connector with easy QC for shoot line 2 piece solid connector with easy QC for monitor line		HSF104-4
	Do not disassemble 2 piece connectors.		ПЭГ 104-4
	Branch Tee		
7	Branch shoot line from 1 line into 2 lines in perpendicular form		HSF105-S
Mark B	Branch shoot line from 1 line into 2 lines in perpendicular form		1101 100-0
	Branch monitor line from 1 line into 2 lines in perpendicular form		HSF105-M
	Brahof monitor and from 1 and 11 to 2 and 5 an porportational arternal		1101 100 111
	Male Connector - SF and MB		
	Connects 2 female ends of unions for shoot line	10 pack	HSF106-S
		•	
	Connects 2 female ends of unions for monitor line	10 pack	HSF106-M
		•	

Sulfuryl Fluoride Equipment



	Fumigation Service & Supply, Inc.		
Sulfuryl Fluoride (S	SF) Fumigation Equipment Description	Sizes	Item #
	Elbow		
186	Union for shoot line at a 90 degree angle		HSF107-S
4	Union for monitor line at a 90 degree angle		HSF107-M
	Reducer - Expander		
	Reduces/expands shoot line to monitor line size or vice versa with		HSF108-S
	easy QC. SF and MB. Don not disassemble HSF108-S.		
	Plug in Reducer - 1 piece reducer from shoot to monitor line		HSF108-M
	Ball Valve		
	Ball valve for shoot line		HSF109-S
V6 (-1)	Ball valve for monitor line		HSF109-M
	Check Valve		
America 12	1 way flow valve for shoot line with easy QC ends		HSF110-S
	1 way flow valve for monitor line with easy QC ends		HSF110-M
	Shoot Line Manifold - 5 Port		
品品品品	Allows you to apply up to 4 cylinders into 1 location, or spread gas up to 4 areas from one cylinder using shoot sized line.		HSF111-S
	Alleron contentrate and contentrate and adjusted and interesting and adjusted and a		HSF111-M
	gas up to 4 areas from one cylinder using monitor sized line.		
	Call FSS, Inc. for custom manifolds and manifolds with valves.		
	Shoot Line Manifold - 7 Port		
	Allows you to apply up to 6 cylinders into 1 location, or spread		HSF112-S
	gas up to 6 areas from one cylinder using shoot sized line.		
0000000	Allows you to apply up to 6 cylinders into 1 location, or spread		HSF112-M
	gas up to 6 areas from one cylinder using monitor sized line.		
	Call FSS, Inc. for custom manifolds and manifolds with valves.		

Sulfuryl Fluoride Equipment



Sulfuryl Fluoride (SE) Fu	unication Equipment Description	Sizes	Itom #
	Imigation Equipment Description ck Mounted Multi Spool System Mounted to receiver hitch on truck - can hold up to 18 shoot line spools or 30 monitor line spools.	Sizes	Item # HSF113
Spo	Manages multiple spools of shoot and monitor line for extended fumigations.		HSF114
Hea	Assists with respooling shoot and monitor line after use for proper storage. High torque and rugged, with speed adjustment which is needed for proper respooling. This is a corded drill.		HSF115
Res	Fits into spool flanges snug to assist with respooling. Requires a 1/2 drill.		HSF116

Metal Phosphide Equipment



<mark>Metal Phosphide Fu</mark>	migation Equipment Description	Sizes	Item #
	Plastic Tarping	12' x 100'	HMP101-1
	Disposable tarping material that comes in different sized rolls.	20' x 100'	HMP101-2
	Holds Phosphine at efficient levels. Cut plastic to any length and	24' x 100'	HMP101-3
	use other sealing material (listed in ACCESSORIES section)	32' x 100'	HMP101-4
	to seal around doors, windows and other gas escape points for	40' x 100'	HMP101-5
	large scale fumigations. HMP101-6 is only 2 mil. thickness.	40' x 450'	HMP101-6
	Top Hatch Poly Seal/Cap		HMP102
To the last	Round railcar polyethylene hatch seal/cover. 30 inches with elastic edge.		
	Top Hatch Remay Filter		HMP103
	Used to place pre-packaged fumigant in rail cars.		
	40 inches permeable material.		
	Fumi-Cel Cloth Bag		HMP104
	Cloth, pleated bags designed specifically for Fumi-Cel applications.		
	Draw string to assist with hanging bags in bins.		
	Fumi-Disc 22		HMP105
	Cardboard disc for application of pre-packaged fumigant.		HIVIP 105
TI DE UP	Attaches to inside of railcar.		
	- Alastio to moid of failure		
ATTENDED TO	Fumi-Disc 33		HMP106
<u> </u>	Larger cardboard disc for application of pre-packaged fumigant.		
THE DE UP	Attaches to inside of railcar.		
100			

Metal Phosphide Equipment



Metal Phosphide F	umigation Equipment Description	Sizes	Item #
	Pellet Probe Applicator (PVC) 5 Ft. tube made of PVC material with cone on top for funneling pellets into grain masses. Probe end at angle for penetration and distribution. Helps prevent bridging.		HMP107
	Pellet Probe Applicator (Aluminum) 8 Ft. tube made of aluminum with cone on top for funneling pellets into grain masses. Probe end at angle for penetration and distribution. Helps prevent bridging.		HMP108
	Pellet Dispenser Automated dispensing device for application of Phosphine pellets.		HMP109
	Re-Circulation Manifold System This system is designed to give even air flow through re-circulation system. Includes a 2 port, 3 port, and 4 port assembly. 9 custom ports with 4 rolls of re-circulation sealing tape.		HMP110
DANGER / PRECAUCION POISON & PELIGNO MICHAEL PRINCE HISTORY HETAL PRINCE	Wire Disposal Basket For containment & deactivation of pre-packaged Metal Phosphides. Needs a dry disposal system. Place used pre-packaged fumigant in basket, and place basket in disposal system.		HMP111
	Dry Disposal System Specially designed drum for locking and containment of disposed pre-packaged Phosphine fumigant. Requires wire disposal basket. Dry disposal systems come in dry drums for 1st step of disposal, and wet drums for final step of disposal that come with water fill and release valves.	dry wet	HMP112-D HMP112-W

Metal Phosphide Equipment



Metal Phosphide Fu	Metal Phosphide Fumigation Equipment Description		Item #
	Re-Circulation System Blower - **		
	Blower designed specifically to re-circulate gas through grain storage structures with high amounts of static pressure. 2 blowers:	low vol.	HMP113-1
	low volume circulation w/ medium air movement/pressure and high volume circulation w/ high air movement/pressure. Both are spark resistant circulatory fans and motor casing/wiring.	high vol.	HMP113-2



Eco2Fume (Eco) Fu	ımigation Equipment Description	Sizes	Item #
	Fum-Adapter Hook up to a cylinder of Eco2Fume Wrench required.		HE101
	Hand Tight Adapter Hook up to a cylinder of Eco2Fume with elbow adapter - either male or female end. No wrench required.	male end femal end	HE101-M HE101-F
	Fumo-Hose (Low Temperature) - ** Flexible hose that can work up to 3000 psi. at 70 F and can withstand extremely low temperatures. Great for ends of Eco application hose where ends tend to freeze. Can order special lengths. Ends same as CO2 and air hose. For monitoring line - HMB103 or HSF103 is used.	10 ft 25 ft 50 ft 100 ft 200 ft	HE102-1 HE102-2 HE102-3 HE102-4 HE102-5
	Fumo-Hose (Standard) Flexible hose that can work up to 2750 psi. at 70 F. Standard hose for universal application methods. Use with any fumigant. Can order special lengths. Ends same as CO2 and air hose. For monitoring line - HMB103 or HSF103 is used.	10 ft 25 ft 50 ft 100 ft 200 ft	HE103-1 HE103-2 HE103-3 HE103-4 HE103-5
	Fumo-Lock Adapter Adapter used to apply gas to a PD railcar or bulk semi trailer. Standards are 3" and 4" but can custom order. Available with and without QC.	3 in. 4 in. 3 in. QC 4 in. QC	HE104-3 HE104-4 HE104-3Q HE104-4Q
	Fumo-Copper System 50 ft. of flexible copper tubing, with ferruled ends for cylinder adapter and extra application equipment accessories. Mainly used in fixed settings, and for regular trailer/container applications. Special lengths can be ordered. Call FSS, Inc.	50 ft	HE105
The state of the s	Fumo-Swivel Union Set This set allows for a male to female end or male to male end application hose connection using swivel mechanism.	M x F only M nipple	HE106-F HE106-M
		set	HE106-B



	runigation Service & Supply, inc.		
Eco2Fume (Eco) Fu	umigation Equipment Description	Sizes	Item #
	Fumo-Swivel Union Female This union allows for a female to female end application hose connection using swivel mechanism.		HE107
	Q.C. Union - ## Quick connect type of union comes with female (nut) end always: Male end (insertion piece) with male threading for hose hookup Male end (insertion piece) with female threading for hose hookup This QC union is check valved at both ends when disconnected. Full flow QC unions available for certain applications. Call for info.	male end femal end	HE108-M HE108-F
	Fumo-Tee All male ends for female connection. Swivel unions commonly associated with this item. Hook up hoses to shoot 2 cylinders into 1 location, or use to spread gas into 2 locations.		HE109
	Fumo-Tee Female 2 female ends and main male end. Swivel unions commonly associated with this item. Hook up hoses to shoot 2 cylinders into 1 location, or use to spread gas into 2 locations.		HE110
	Fumo-Cross 4 female ends for male connection. Swivel unions commonly associated with this item. Hook up hoses to shoot 1-3 cylinders into 1 location, or use to spread gas into 1-3 locations.		HE111
	Fumo-Bow Union for shoot line at a 90 degree angle. Swivel unions commonly associated with this item. male to male male to female (Street) female to female	M x M M x F	HE112-M HE112-S
		FxF	HE112-F



Eco2Fume (Eco) Fur	migation Equipment Description	Sizes	Item #
	Fumo-Plug		
	Male end plug for end of application hose or for openings on tee, cross, elbow, or manifolds when not in use but have gas inside.	male plug	HE113-M
	Female end cap for end of application hose or for openings on tee, cross, elbow, or manifolds.	female cap	HE113-F
	Fumo-Cog - ##		
	Restricts amount of gas applied to a known timed interval:		
W W W	.02 regulates flow to approximately .5 lbs / minute or 30 lb / hr .03 regulates flow to approximately 1 lbs / minute or 60 lb / hr .04 regulates flow to approximately 1.5 lbs / minute or 120 lb / hr This method is sometimes used with SF.		HE114-2 HE114-3 HE114-4
	Fumo-Rod - ##	12 inch	HE115
	Used at the end of application hose usually with valve to apply Eco into very tight crevices, such as between trailer doors, bin tops, or into bags. Comes 12 inch standard, but can be custom length. Can shape in certain fashions before delivery for specific purposes. Call FSS, Inc. for more information.		
	Fumo-Valve		HE116
Sounds	Used at the end of application hose usually with application equip. Controls flow of Eco into target area. High pressure rated.		
	Manifold - ##	3 port - 1 out	HE117-3
	Comes with a pressure gauge for safety. Attach multiple	4 port - 1 out	
	application hoses for larger fumigations. Standard manifolds come	5 port - 1 out	
OTTT	with 3 to 6 ports. Call FSS, Inc. for custom and spider manifolds. Come w/ QC fittings by adding Q after item number, eg -HC117-4Q Come w/ valves by adding V after item number, e.g HC117-6V	6 port - 1 out	
	Fumo-Rack		HE118
	Use when you don't have enough cylinders for a full rack Eco2fume for shipment, or for storage purposes. Fabricated steel cage.		



Eco2Fume (Eco) Fumigation Equipment Description

Sizes

Item #

When (-##) appears behind description - DO NOT DISASSEMBLE the tube fitting at the end of equipment.







Bulkheads are used for bins and problematic equipment hard to reach as a permanent solution. Many systems can be manufactured. Call FSS, Inc.



Transfill Systems

FSS, Inc. can fabricate Transfill systems for Eco2Fume and for air supply cylinders. We do not offer 1 type of system due to a wide variety of customer requests. Contact us if you would like assistance w/ development or fabrication of safe Transfill systems.



VaporPH3os Equipment



VaporPH3os (Vph) Fumigation Equipment Description	Sizes	Item #
Nitrogen Cylinder Adapter Hook up to a cylinder of Nitrogen for use on HDS machine. Wrench required.		HV101
Hand Tight Adapter Hook up to a cylinder of Nitrogen for use on HDS machine. No wrench required.		HV101-H
Vph Cylinder Adapter Hook up to a cylinder of Vph Wrench required.		HV102
Hand Tight Adapter Hook up to a cylinder of Vph No wrench required.		HV102-H
(Horn Diluphos System) HDS 800 195 Grams per minute		HV103
HDS 200 47 grams per minute		HV104
HDS 80 19 grams per minute		HV105
HDS CF9 6 grams per minute		HV106



Carbon Dioxide (CC	D2) Fumigation Equipment Description	Sizes	Item #
	CO2 Cylinder Adapter Hook up to a cylinder of CO2 Wrench required.		HC101
	Hand Tight Adapter Hook up to a cylinder of CO2 No wrench required.		HC101-H
	Application Hose (Low Temperature) - ** Flexible hose that can work up to 3000 psi. at 70 F and can withstand extremely low temperatures. Great for ends of CO2 application hose where ends tend to freeze. Can order special lengths. Ends same as Eco and air hose.	10 ft 25 ft 50 ft 100 ft 200 ft	HC102-1 HC102-2 HC102-3 HC102-4 HC102-5
	Application Hose (Standard) Flexible hose that can work up to 2750 psi. at 70 F. Standard hose for universal application methods. Use with any fumigant. Can order special lengths. Ends same as Eco and air hose.	10 ft 25 ft 50 ft 100 ft 200 ft	HC103-1 HC103-2 HC103-3 HC103-4 HC103-5
	CO2 Monitor Line Specialized line designed to hold CO2 for accurate readings. CO2 is a volatile gas that can escape most materials, but not this. Use SF connectors with this tubing for monitoring purposes. Comes only in 25 ft. sections.	25 ft	HC104
	Copper Application System 50 ft. of flexible copper tubing, with ferruled ends for cylinder adapter and extra application equipment accessories. Mainly used in fixed settings, and great for regular trailer/container applications. Special lengths can be ordered. Call FSS, Inc.	50 ft	HC105
167	2 Piece Swivel Union Set This set allows for a male to female end or male to male end application hose connection using swivel mechanism.	M x F only M nipple	HC106-F HC106-M
		set	HC106-B



Carbon Dioxide (Co	D2) Fumigation Equipment Description	Sizes	Item #
	Female Swivel Union		HC107
	This union allows for a female to female end application hose connection using swivel mechanism.		
1 =/1	Q.C. Union - ##		
	Quick connect type of union comes with female (nut) end always: Male end (insertion piece) with male threading for hose hookup Male end (insertion piece) with female threading for hose hookup This QC union is check valved at both ends when disconnected. Full flow QC unions available for certain applications. Call for info.	male female	HC108-M HC108-F
	Branch Tee		HC109
	All male ends for female connection. Swivel unions commonly associated with this item. Hook up hoses to shoot 2 cylinders into 1 location, or use to spread gas into 2 locations.		
	Branch Tee Female		HC110
	2 female ends and main male end. Swivel unions commonly associated with this item. Hook up hoses to shoot 2 cylinders into 1 location, or use to spread gas into 2 locations.		
	Cross		HC111
	4 female ends for male connection. Swivel unions commonly associated with this item. Hook up hoses to shoot 1-3 cylinders into 1 location, or use to spread gas into 1-3 locations.		
	Elbow	M x M	HC112-M
	Union for shoot line at a 90 degree angle. Swivel unions commonly		
	associated with this item. male to male male to female (Street) female to female	MxF	HC112-S
		FxF	HC112-F



	Fumigation Service & Supply, Inc.		
arbon Dioxide (CO2	2) Fumigation Equipment Description	Sizes	Item #
	Plug Male end plug for end of application hose or for openings on tee, cross, elbow, or manifolds when not in use but have gas inside. Female end cap for end of application hose or for openings on tee, cross, elbow, or manifolds.	male plug female cap	HC113-M HC113-F
	Restrictor Cog - ## Restricts amount of gas applied to a known timed interval: .02 regulates flow to approximately .5 lbs / minute or 30 lb / hr .03 regulates flow to approximately 1 lbs / minute or 60 lb / hr .04 regulates flow to approximately 1.5 lbs / minute or 120 lb / hr This method is sometimes used with SF.		HC114-2 HC114-3 HC114-4
	Application Rod - ## Used at the end of application hose usually with valve to apply CO2 into very tight crevices, such as between trailer doors, bin tops, or into bags. Comes 12 inch standard, but can be custom length. Can shape in certain fashions before delivery for specific purposes. Call FSS, Inc. for more information.	12 inch	HC115
	Control Valve Used at the end of application hose usually with application equip. Controls flow of CO2 into target area. High pressure rated.		HC116
	Manifold - ## Comes with a pressure gauge for safety. Attach multiple application hoses for larger fumigations. Standard manifolds come	3 port - 1 out 4 port - 1 out 5 port - 1 out	HC117-4



Manifold - ##

Comes with a pressure gauge for safety. Attach multiple
application hoses for larger fumigations. Standard manifolds come
with 3 to 6 ports. Call FSS, Inc. for custom and spider manifolds.
Come w/ QC fittings by adding Q after item number, eg -HC117-4Q
Come w/ valves by adding V after item number, e.g. - HC117-6V

Tarping Material CO2

HC117-3
4 port - 1 out
HC117-4
5 port - 1 out
HC117-5
6 port - 1 out
HC117-5
HC117-6
HC118

CO2 is a very volatile gas and only certain polymers can block its escape. Other tarping material **CANNOT** be substituted for CO2 applications. High levels of CO2 in ambient air can be dangerous. Comes in 78 ft. wide sections and in increments of 25 ft. long - up to 300 ft. Specify length when ordering.




Carbon Dioxide (CO2) Fumigation Equipment Description

Sizes

Item #

HC119



Carbon Dioxide Safety Training

If you are interested in using CO2 to fumigate stored product pests and for other uses, this would be a great tool. Power Point and limited consultation also included.

FSS, Inc. CO2 Designs

FSS, Inc. has designed CO2 application systems delivering extremely large amounts in a safe setting. Please contact us to assist in developing the CO2 system that meets your specific needs.

When (-##) appears behind description - DO NOT DISASSEMBLE the tube fitting at the end of equipment.



Accessories for all typ	es of Fumigations	Sizes	Item #
A	ir Cylinder Adapter Hook up to a cylinder of air for refilling SCBA tanks. Wrench required.		HA101
H	and Tight Adapter Hook up to a cylinder of air for refilling SCBA tanks. No wrench required.		HA101-H
A	ir Filling Line for SCBA This single valved system fills SCBA Tanks for standard 2100 psi. Hose is designed to work at 2750 psi. Longer hose upon request. The glycerin pressure gauge can withstand up to 5000 psi. Special design for air cylinders only !!!!!!!!	6 ft	HA102
Se	SCBA with full face mask - check/alarm gauge - Without Cylinder SCBA comes with an aluminum cylinder and full face mask. 2100 psi cylinder and necessary pressure check/alarm gauge. SCBA comes with a composite cylinder and full face mask.		HA103 HA103-A HA103-C
Se	2100 psi cylinder and necessary pressure check/alarm gauge. CBA Cylinder - ** Aluminum Cylinder - Check with your local Fire Dept. for scheduled maintenance. Composite Cylinder - Check with your local Fire Dept. for scheduled maintenance.		HA104-A HA104-C
Section	CBA Carrying Case This case is molded to fit your SCBA for protection during transportation. Highly recommended if transporting SCBA.		HA105
Fa	Full face mask uses canisters that filter toxins out of ambient air. Mask does not protect against an Oxygen deficient atmosphere. Fits almost any face size. Comes in small - medium - large	small medium large	HA106-S HA106-M HA106-L



ccessories for all types of Fumigations	Sizes	Item #
Canister for Face Mask		
Phosphine Gas Cartridge - Use in up to 15 ppms of Phosphine.		HA107-P
Organic Vapors Cartridge		HA107-O
Bin/Space Entry Cage		
Safely and comfortably enter grain bins and confined spaces. Safer than a bosens chair.	18"	HA108-1
	24"	HA108-2
Application Hose (High Pressure) - **	10 ft.	HA109-1
Flexible hose that can work up to 5000 psi. at 70 F.	25 ft.	HA109-2
Used mainly with Vaporizer in Methyl Bromide applications.	50 ft.	HA109-3
Use with any fumigant - even CO2.	100 ft.	HA109-4
Can order special lengths. Ends same as Eco, CO2, and air hose. Special ends can be substituted for Vaporizer attachment.	200 ft.	HA109-5
Steel Braided Hose - **	10 ft.	HA110-1
Very durable hose with steel braided protection. Works up to	25 ft.	HA110-2
3500 psi. at 70 F. Used mainly with Vaporizer in MB applications.	50 ft.	HA110-3
Use with any fumigant - even CO2.	100 ft.	HA110-4
Can order special lengths. Ends same as Eco, CO2, and air hose.		
Special ends can be substituted for Vaporizer attachment.		
Specialty Sealing Bags For small fumigations, save time and money with quick and easy	3' x 3' x 3'	HA111-1
setup and breakdown. Three sizes - Oversized. 4 mil. Thickness - Comes 25 bags per roll.	4' x 4' x 4'	HA111-2
For large rolls of plastic ranging from 12 ft. to 40 ft. wide and up to	5' x 5' x 5'	HA111-3
400 ft. long, see METAL PHOSPHIDE section item # HMP101.		
Tarping Material - **		
This highly durable fiber reinforced material is the best gas		HA112
impermeable material on the market. Holds Methyl Bromide,		
Sulfuryl Fluoride, and Phosphine gas, with high efficiency.		
Sulfuryl Fluoride, and Phosphine gas, with high efficiency. Comes in 78 ft. wide sections and in increments of 25 ft. long - up to 300 ft. Specify length when ordering.		



	Fumigation Service & Supply, Inc.		
ccessories for all ty	ypes of Fumigations	Sizes	Item #
	Re-circulation Sealing Tape - Water Proof	roll	HA113
0	Gas impermeable - Strong, durable, elastic tape designed to seal joints of corrugated drainage pipe commonly used to re-circulate Phosphine gas in grain structures. 8 mil. Tensile Str20 lbs/sq.in. Each roll - 108 ft. x 2 in Each case - 24 rolls. Can also use on venting hose joints.	case	HA113-C
	Brown Sealing Tape	roll	HA114
	Tape designed to stick to plastic and surface to create a gas impermeable seal. Tape can be used for many purposes. Each roll - 120 ft. x 3 in Each case - 16 rolls.	case	HA114-C
	Spray Adhesive Help tarps stick to tape in colder weathers. Also used to	can	HA115
Pal Barn-Tack Mgh tick Spray Athesive	create a seal on porous material such as concrete and brick. Apply as needed. This spray helps adhere to wet surfaces. Each can - 12 oz Each case - 12 cans.	case	HA115-C
1	Fire Rated Expansion Foam For sealing walls at fire break areas. Not affected by moisture. Seals concrete, brick, wood, metal, aluminum, steel. 24 oz. can fills 1 cubic foot.	can	HA116
	Sand Snake - ** Use this sand filled sleeve to create a pressure seal on large tarped fumigations. 25 per order. Durable vinyl material with triple seam. Material WILL Last in all weather conditions.		HA117-S
	Corner Covers - durable sleeves that cover the corners of a trailer or "boxed" fumigation to protect tarp. 4 per order.		HA117-C
	Cylinder Scale		
	300 lb. maximum capacity. 1.375 in. tall. 9.25" x 9.25. platform. Digital readout. Measures exact dosage for cylinderized fums.		HA118
	Can add 400 lb. capacity.	400 lb.	HA118-1
	Can substitute for a 14 in. x 14 in. platform.	14 x 14	HA118-2
	Can add both 400 lb. capacity and 14 in. x 14 in. platform.	complete	HA118-3



Pallet Scale Place pallets of cylinders or equipment of any type for exact measurement. 5500 lb. maximum capacity. Measures kg & lbs. 4' x 4' platform. Digital readout. Can add a ramp for assisting cylinders on and off of scale. Can add 2 ramps. Cylinder Scale - Heavy Duty 1000 lb. maximum capacity. 4 in. tall. 15 in. x 15 in. platform. Digital readout. Measures exact dosage for cylinderized fums. Can add a ramp for assisting cylinders on and off of scale. Can substitute for a 24 in. x 24 in. platform. Digital readout. Measures exact dosage for cylinderized fums. Can add a ramp for assisting cylinders on and off of scale. Veramp HA120-1 Can substitute for a 24 in. x 24 in. platform. 24 in. Platform with ramp. Surface Thermometer Hold a few inches away from product or surface and pull trigger to get immediate, accurate temperature in a digital readout. Uses a laser sight, up to 750 F. Probe Thermometer - ** Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated furnigations40 to 150 C. Look in USDA section for other thermometer models. Temperature Gauge - ** Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Furnigation Timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals.		Tulinguiton Service & Supply, inc.		
Place pallets of cylinders or equipment of any type for exact measurement. 5500 lb. maximum capacity. Measures kg & lbs. 4 x 4' platform. Digital readout. Can add a ramp for assisting cylinders on and off of scale. Can add 2 ramps. Cylinder Scale - Heavy Duty 1000 lb. maximum capacity. 4 in. tall. 15 in. x 15 in. platform. Digital readout. Measures exact dosage for cylinderized fums. Can add a ramp for assisting cylinders on and off of scale. Can add a ramp for assisting cylinders on and off of scale. Can add a ramp for assisting cylinders on and off of scale. Can add a ramp for assisting cylinders on and off of scale. Can add a ramp for assisting cylinders on and off of scale. Can add a ramp for assisting cylinders on and off of scale. W / ramp HA120-1 24 x 24 HA120-2 24 in. Platform with ramp. W / ramp HA120-3 Surface Thermometer Hold a few inches away from product or surface and pull trigger to get immediate, accurate temperature in a digital readout. Uses a laser sight, up to 750 F. Probe Thermometer - ** Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated fumigations40 to 150 C. Look in USDA section for other thermometer models. Temperature Gauge - ** Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Fumigation Timer Highly accurate and dependable. This is a rugged timer Highly accurate and dependable. This is a rugged timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals.	Accessories for all type	es of Fumigations	Sizes	Item #
4' x 4' platform. Digital readout. Can add a ramp for assisting cylinders on and off of scale. Can add 2 ramps. Cylinder Scale - Heavy Duty 1000 lb. maximum capacity. 4 in. tall. 15 in. x 15 in. platform. Digital readout. Measures exact dosage for cylinderized fums. Can add a ramp for assisting cylinders on and off of scale. Can abd a ramp for assisting cylinders on and off of scale. Can substitute for a 24 in. x 24 in. platform. 24 x 24 HA120-2 24 in. Platform with ramp. Surface Thermometer Hold a few inches away from product or surface and pull trigger to get immediate, accurate temperature in a digital readout. Uses a laser sight, up to 750 F. Probe Thermometer - ** Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated fumigations40 to 150 C. Look in USDA section for other thermometer models. Temperature Gauge - ** Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Fumigation Timer Highly accurate and dependable. This is a rugged timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals.	Pa	Place pallets of cylinders or equipment of any type for exact		HA119
Can add 2 ramps. Cylinder Scale - Heavy Duty 1000 lb. maximum capacity. 4 in. tall. 15 in. x 15 in. platform. Digital readout. Measures exact dosage for cylinderized fums. Can add a ramp for assisting cylinders on and off of scale. Can substitute for a 24 in. x 24 in. platform. 24 x 24 HA120-2 24 in. Platform with ramp. Surface Thermometer Hold a few inches away from product or surface and pull trigger to get immediate, accurate temperature in a digital readout. Uses a laser sight, up to 750 F. Probe Thermometer - ** Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated fumigations40 to 150 C. Look in USDA section for other thermometer models. Temperature Gauge - ** Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Fumigation Timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals.		4' x 4' platform. Digital readout.		
1000 lb. maximum capacity. 4 in. tall. 15 in. x 15 in. platform. Digital readout. Measures exact dosage for cylinderized fums. Can add a ramp for assisting cylinders on and off of scale. Can substitute for a 24 in. x 24 in. platform. 24 x 24 HA120-2 24 in. Platform with ramp. Surface Thermometer Hold a few inches away from product or surface and pull trigger to get immediate, accurate temperature in a digital readout. Uses a laser sight, up to 750 F. Probe Thermometer - ** Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated fumigations40 to 150 C. Look in USDA section for other thermometer models. Temperature Gauge - ** Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Fumigation Timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals.	0 FSS	Can add 2 ramps.	•	
Can add a ramp for assisting cylinders on and off of scale. Can substitute for a 24 in. x 24 in. platform. 24 x 24 HA120-2 24 in. Platform with ramp. Surface Thermometer Hold a few inches away from product or surface and pull trigger to get immediate, accurate temperature in a digital readout. Uses a laser sight, up to 750 F. Probe Thermometer - ** Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated fumigations40 to 150 C. Look in USDA section for other thermometer models. Temperature Gauge - ** Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Fumigation Timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals.	Су	1000 lb. maximum capacity. 4 in. tall. 15 in. x 15 in. platform.		HA120
Surface Thermometer Hold a few inches away from product or surface and pull trigger to get immediate, accurate temperature in a digital readout. Uses a laser sight, up to 750 F. Probe Thermometer - ** Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated fumigations40 to 150 C. Look in USDA section for other thermometer models. Temperature Gauge - ** Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Fumigation Timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals.	d Table	Can add a ramp for assisting cylinders on and off of scale. Can substitute for a 24 in. x 24 in. platform.	24 x 24	HA120-2
Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated fumigations40 to 150 C. Look in USDA section for other thermometer models. Temperature Gauge - ** Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Fumigation Timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals.	Su	Hold a few inches away from product or surface and pull trigger to get immediate, accurate temperature in a digital readout.		HA121
Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to record remotely. AC powered with battery backup. Fumigation Timer Highly accurate and dependable. This is a rugged timer Comes in 1 hour or 24 hour time intervals. 1 hour HA124-1	Pro	Use probe to get core temperatures on commodities or products with digital readout. Single zone temperature range -40 to 300 F. Can be used for USDA regulated fumigations40 to 150 C.		HA122
Highly accurate and dependable. This is a rugged timer 1 hour HA124-1 Comes in 1 hour or 24 hour time intervals.	Tel	Records continuous temperature in weekly increments. Keeps written record of specific location temperature. Can be ordered to		HA123
Comes in 1 hour or 24 hour time intervals.	Fu	<u> </u>	1 hour	UA424.4
24 hour HA124-2	2	- · · · · · · · · · · · · · · · · · · ·		
	D D		24 hour	HA124-2



	Fumigation Service & Supply, Inc.		
Accessories for all types	s of Fumigations	Sizes	Item #
OF-SS	iler Vent Great for venting trailers of all types, while they are locked.		HA125
Re-	circulation Fan - ** Re-circulates gas in tarped or trailer fumigations. Rugged and long-lasting. Steel wire cage. 3 speeds - 24 in. circum. 1 fan pushes enough air for 3000 - 4000 cubic ft. re-circulation.	24 inch 18 inch	HA126-1 HA126-2
High	 h Powered Fan for Venting Very durable in all weather conditions - Can supply power option. Fans are designed to push large volumes of air with resistance for extended times. cfm depends on amount of static pressure. 12 in. circum with .75 HP motor - produces up to 2500 cfm 18 in. circum with 1.5 HP motor - produces up to 5000 cfm 	12" 18"	HA127-1 HA127-2
Re-	Circulation Blower - ** This blower creates a closed system of air. 4 in. openings. Pushes air through hose to exterior of building. Great for outdoors. Small blower for venting small fumigations w/ reinforced vent hose. Medium blower for venting fumigations with reinforced vent hose.	small medium	HA128-1 HA128-2
Reit	forced Venting Hose Gas impermeable venting hose. Use to capture gas to purge out of structures. Comes in 25 ft or 50 ft. sections. Use re-circulation sealing tape to create an air tight seal.	4" - 25 ft. 12" - 25 ft. 18" - 25 ft. 4" - 50 ft. 12" - 50 ft. 18" - 50 ft.	HA129-1 HA129-2 HA129-3 HA129-4 HA129-5 HA129-6
Ven	Connect 2 sections of venting hose to create longer lengths with this aluminum connector. Use re-circulation sealing tape to create an air tight seal.	4 inch 12 inch 18 inch	HA130-1 HA130-2 HA130-3



	rumigation Service & Supply, Inc.		
Accessories for all types	s of Fumigations	Sizes	Item #
On	Site Cylinder Dolly Haul cylinders around with ease. NOT FOR PUBLIC ROAD USE! Cylinders attach to back of vehicle for job site use. Sturdy attachment to hitch of truck. Secures many cylinder types.		HA131
Tub	This cuts 3/8 in. and 1/4 in. Methyl Bromide and Sulfuryl Fluoride tubing (shoot and monitor line) with ease and with a perfect cut every time.		HA132
Spe	Reel up your shoot line hose and keep it protected when not in use. Reels up to 200 ft. of 1/2 in. OD hose.		HA133
Hea	6 inch plain block with safety hook. 6000 lb. max. capacity. Holds up to 3/4 inch cable. Solid steel with bronze bearing. Corrosion resistant. Removable grade 5 heat treated fasteners.		HA134
Hea	Adlamp Attaches to head and/or hardhat. Bright 1 Watt super high-flux Luxeon LED (50,000 hour life) Great for confined spaces and night tasks.		HA135
Fing	gerless Sealing Gloves Great for when hand protection is needed and still have the versatility of your fingers.		HA136



	rumigation Service a Supply, Inc.		
Accessories for all	types of Fumigations	Sizes	Item #
	Fumigator's Pouch Holds standard can of adhesive spray and utility knife. Attaches to belt loop.		HA137
	Line Labeling Device Organizational numbering device for labeling gas application and monitoring lines. Legend 0 - 9. Polyester tape. Withstands temperatures from -40 to 250 degrees F.		HA138
6	Oxygen Cylinder Adapter Hook up to a cylinder of Oxygen for multiple uses. Wrench required.		HA139
	Hand Tight Adapter Hook up to a cylinder of Oxygen for multiple uses. No wrench required.		HA139-H
	Cylinder Wall Brace		
	Secures 1 cylinder to a wall with chain wrap Screws not included because each wall requires different mounting.	1 brace	HA140-1
	Secures 2 cylinder to a wall with chain wrap Custom Wall Braces can be made larger than dual braces Call for custom braces larger than 2	dual brace	HA140-2
sa-st	Fumigation Wrench Open all types cylinders and fasten all connections to all hoses with ease using this 1 wrench. This is a life saver for all types of fumigations.		HA141
	Pipe Tape Use to assist in sealing joints to certain application hose. Use when retightening joints. It is important to get a good seal on all of your fumigation equipment for safety reasons.		HA142



Accessories for all t	ypes of Fumigations	Sizes	Item #
	Pressure Gauge Used if there is more than one cylinder of CO2 or Eco2Fume being applied in a fumigation. Always check gauge for safe handling.		
	Reads up to 3000 psi liquid filled. Medium pressure gauge up to 600 psi liquid filled. Low pressure gauge for pressure up to 60 psi.	3000 psi 600 psi 60 psi	HA143-H HA143-M HA143-L
-	Face Shield All polycarbonate material face shield with adjustable headgear. Always use face protection when applying cylinderized gas.		HA144
	Disposable Venting Hose This is a cheap alternative for venting hose if fumigations are not always	4 inch	HA145-1
	local. Cut to the size needed. All rolls are 6 mil 4 in. & 12 in. comes in 1000 ft. rolls and 18 inch comes in 500 ft. rolls.	12 inch	HA145-2 HA145-3

Warning Placards



Warning Placard De	scription - All Placards are Red Lettered	Sizes	Item #
□Q+ DANGER - PELIGRO □Q+	Methyl Bromide Warning Placard - **		
POISON GAS	Contains all Emergency Contact information and fits legal		
METHYL BROMIDE	requirements. English and Spanish Warning announcement.		
DO NOT ENTER/NO ENTRE	250 Placards per box		HW101
	50 laminated Placards		HW101-L
The same of the sa	50 laminated Placards with magnetic strips		HW101-M
DANGER-FUMIGATION PELIGRO-FUMIGACION	Sulfuryl Fluoride Warning Placard - **		
PURCASING CAS RESCRIPTION	Contains all Emergency Contact information and fits legal		
DEADLY POISON HIGHWOOD IN THE WARRING TO HELD AND THE PROPERTY AND THE PR	requirements. English and Spanish Warning announcement.		
THE PARTY NAMED AND ADDRESS OF	250 Placards per box		HW102
A Division of the Control of the Con	50 laminated Placards		HW102-L
	50 laminated Placards with magnetic strips		HW102-M
DANICER/PELICED	Aluminum Phosphide Warning Placard - **		
Station And Or Community Under Famousing DO NOT ENTER/NO ENTRE	Contains all Emergency Contact information and fits legal		
PHOSPHINE GAS	requirements. English and Spanish Warning announcement.		
The Discount of Sandy Asing State Control	250 Placards per box		HW103
SECTION SECTIO	50 laminated Placards		HW103-L
Amico saledos	50 laminated Placards with magnetic strips		HW103-M
DANGER/PELICED	Magnesium Phosphide Warning Placard - **		
Stratus And St Connecting Under Foreigning - DO NOT ENTER/IND ENTIRE	Contains all Emergency Contact information and fits legal		
PHOSPHINE GAS	requirements. English and Spanish Warning announcement.		
The Discount of Sandy Asing State Control	250 Placards per box		HW104
SEASON SE	50 laminated Placards		HW104-L
Panera ementor	50 laminated Placards with magnetic strips		HW104-M
ANGER/PELIGRO	Eco2Fume Warning Placard - **		
Poison Gas Hydrogen Phosphide-Phesphine-PH, Cartom Divide-CO,	Contains all Emergency Contact information and fits legal		
DO NOT ENTER/ NO ENTRE HIS ENCLOSURE IS BEING FURNIGATED WITH	requirements. English and Spanish Warning announcement.		
ECO ₂ FUME	250 Placards per box		HW105
	50 laminated Placards		HW105-L
	50 laminated Placards with magnetic strips		HW105-M
DANGER/PELIGRO	VaporPH3os Warning Placard		
Poison Gas Prosphide-Phasphine-PH, Carton Olexide-CO;	Contains all Emergency Contact information and fits legal		
Carton Diexide-CO; Area And Or Commodity Under Famigation - DO NOT ENTER/NO ENTRE THIS ENCLOSURE IS HENG FUNGATED WITH VAPORPH ₃ OS	requirements. English and Spanish Warning announcement.		
VAPORPH, OS	250 Placards per box		HW106
	50 laminated Placards		HW106-L
GHE.	50 laminated Placards with magnetic strips		HW106-M

Warning Placards



Warning Placard De	escription - All Placards are Red Lettered	Sizes	Item #
OANGER-PELIGRO	Carbon Dioxide Warning Placard		
POISON GAS	Contains all Emergency Contact information and fits legal		
CARBON DIOXIDE - CO2	requirements. English and Spanish Warning announcement.		
DO NOT ENTER NO ENTRE	250 Placards per box		HW107
THE RESERVE TO THE RE	50 laminated Placards		HW107-L
The same of the sa	50 laminated Placards with magnetic strips		HW107-M
0 " 10 :1 1	General Pesticide Warning Placard		
DO NOT ENTER /	Contains all Emergency Contact information and fits legal		
NO ENTRE	requirements. English and Spanish Warning announcement.		
Pesticides Being Used	250 Placards per box		HW108
in many of any source and 500 or mobile	50 laminated Placards		HW108-L
The second second	50 laminated Placards with magnetic strips		HW108-M
200	Plastic Envelope Sleeve		
ACCOUNT OF BUILDING	Plastic sleeves that seal placard inside & adhere to any surface.		
0.4188	Totally transparent and keeps the weather off. Sleeves are 14" x 14".		
Charles of the	500 sleeves per order		HW109
	2000 sleeves per box		HW109-B

Security Equipment



	Fumigation Service & Supply, Inc.		
Fumigation Security E	quipment Description	Sizes	Item #
CI	lam Shell Lock - Handle/Lever Place over a door handle/lever - Secures door from original key entry. Can be keyed alike or separate. No need for additional padlock. Made from cast aluminum.		HS101
CI	lam Shell Lock - Knob		HS102
	Place over a door knob - Secures door from original key entry. Can be keyed alike or separate. No need for additional padlock. Made from cast aluminum.		
2	Piece Key 2 Piece key will separate in the keyhole and can only be removed with its own counterpart. No other key can be placed in keyhole, making it impossible to unlock original lock. Minimum order - 50 Keys - Need original lock manufacturer and lock number to order.		HS103
G	as Cylinder Lock		HS104
	Attaches to the valve of the cylinder and prevents tampering with that valve. Padlock is needed and sold separately.		
Ki	ing Pin Lock Solid Steel lock attaches to trailer 5th wheel preventing hookup. Can be keyed alike or separate.		HS105
G	lad Hands Lock Attaches to the Hydraulic sliding "Glad Hands" of trailer preventing hookup to all lines. Keyed alike or separate. Made from cast aluminum.		HS106

Security Equipment



Fumigation Security Equipment Description Sizes Item # **Padlock** HS107 Standard steel padlock - includes 2 keys. Keyed alike. 4 pins in locking mechanism. 5/8 in. shackle height and width. Weather resistant. Padlock - Long Shackle **HS108** Standard steel padlock with long shackle - includes 2 keys. Keyed different. 4 pins in locking mechanism. 2 in. shackle height and 3/4 in. shackle width. Weather resistant. **Padlock - Combination HS109** Standard steel padlock that uses combination lock. Includes 1 change key. 3 dial combination that is resettable. 1 in. shackle height and 3/4 in. shackle width. Weather resistant.

Payment Terms

All credit accounts are payable within 30 days of purchase date. Finance charges will be assessed at a periodic rate of 1.5% per month (Annual Percentage Rate of 18%). Shipments will not be made to accounts with an overdue balance.

Credit Card Policy

We accept Visa, MasterCard, or American Express. Terms available with approved credit application.

Sales Tax

Applicable sales tax will be added. If a customer is tax exempt, provide an exemption certificate when order is placed or sales tax will be charged.

Price Notification

Prices are subject to change without prior notice. The price in effect at shipment will prevail. We will make an effort to keep our customers up to date on price changes. Please confirm a current price at the time orders are placed. A \$50 U.S. Dollar minimum is required on all orders. There will be a \$5.00 U.S. Dollar processing fee placed on orders less than \$50 U.S. Dollars.

Freight Policy

All shipments are made F.O.B. (Freight on Board) shipping point unless otherwise specified. Orders will be shipped pre-paid freight and added to the invoice. We will try to get all orders shipped as soon as possible.



Damaged Freight

Shipments that arrive with missing merchandise or damaged items should be noted on the delivery receipt along with the signature of the driver and a printed record of the driver's name. Report all damaged shipment claims within 24 hours.

Return for Credit

No merchandise shall be returned for credit without the prior approval of Fumigation Service & Supply, Inc. Returns may not be accepted after 14 days of receipt, and the customer will be notified of the acceptance for credit. Any merchandise returned, except where Fumigation Service & Supply, Inc. is at fault, will be responsible for freight charges both ways, and assessed a 15% restocking fee.

Disclaimer

No warrantee is implied or made by FFS, Inc. concerning these products or their use, except that they conform to their original manufacturer label specifications. FSS, Inc. will not be liable for damages resulting from handling, storage, or misuse of these items.

Substitution of Equipment

All equipment/fittings that pertain to a specific gas application procedure or system **ARE NOT** to be substituted for alternatives for different gas application systems due to the fact that all equipment in a system works for that specific pressure and cylinder type. Substitutions may cause serious bodily injury or damage equipment and/or cylinders.

Quotation

We will quote on larger quantities of items listed in this publication. We will also quote on products not listed in this catalog.

